

WHAT IS CLAIMED IS:

1. A method of treating a hydrocarbon containing formation in situ, comprising:
5 providing heat from one or more heat sources to at least one portion of the formation;
allowing the heat to transfer from the one or more heat sources to a selected section of the formation;
controlling the heat from the one or more heat sources such that an average temperature within at least a majority of the selected section of the formation is less than
10 about 375 °C; and
producing a mixture from the formation.
2. The method of claim 1, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources
15 pyrolyzes at least some hydrocarbons within the selected section of the formation.
3. The method of claim 1, wherein controlling formation conditions comprises maintaining a temperature within the selected section within a pyrolysis temperature range.
20
4. The method of claim 1, wherein the one or more heat sources comprise electrical heaters.
5. The method of claim 1, wherein the one or more heat sources comprise surface
25 burners.
6. The method of claim 1, wherein the one or more heat sources comprise flameless distributed combustors.
- 30 7. The method of claim 1, wherein the one or more heat sources comprise natural distributed combustors.

50037

providing heat from one or more heat sources to at least a portion of the formation; and

allowing the heat to transfer from the one or more heat sources to a selected section of the formation such that a porosity of a majority of at least a portion of the selected section increases substantially uniformly.

2271. The method of claim 2270, wherein the one or more heat sources comprise at least two heat sources, and wherein superposition of heat from at least the two heat sources pyrolyzes at least some hydrocarbons within the selected section of the formation.

2272. The method of claim 2270, further comprising maintaining a temperature within the selected section within a pyrolysis temperature range.

2273. The method of claim 2270, wherein the one or more heat sources comprise electrical heaters.

2274. The method of claim 2270, wherein the one or more heat sources comprise surface burners.

2275. The method of claim 2270, wherein the one or more heat sources comprise flameless distributed combustors.

2276. The method of claim 2270, wherein the one or more heat sources comprise natural distributed combustors.

2277. The method of claim 2270, further comprising controlling a pressure and a temperature within at least a majority of the selected section of the formation, wherein the pressure is controlled as a function of temperature, or the temperature is controlled as a function of pressure.

9 2278. The method of claim 2270, further comprising controlling the heat such that an average heating rate of the selected section is less than about 1 °C per day during pyrolysis.

Sub 4 2279. The method of claim 2270, wherein providing heat from the one or more heat sources to at least the portion of formation comprises:
heating a selected volume (V) of the hydrocarbon containing formation from the one or more heat sources, wherein the formation has an average heat capacity (C_v), and wherein the heating pyrolyzes at least some hydrocarbons within the selected volume of the formation; and

10 wherein heating energy/day provided to the volume is equal to or less than Pwr , wherein Pwr is calculated by the equation:

$$Pwr = h * V * C_v * \rho_B$$

15 wherein Pwr is the heating energy/day, h is an average heating rate of the formation, ρ_B is formation bulk density, and wherein the heating rate is less than about 10 °C/day.

2280. The method of claim 2270, wherein allowing the heat to transfer comprises transferring heat substantially by conduction.

20 Sub 5 2281. The method of claim 2270, wherein providing heat from the one or more heat sources comprises heating the selected section such that a thermal conductivity of at least a portion of the selected section is greater than about 0.5 W/(m °C).

25 2282. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons having an API gravity of at least about 25°.

30 2283. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and

wherein about 0.1 % by weight to about 15 % by weight of the condensable hydrocarbons are olefins.

15 2284. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises non-condensable hydrocarbons, and wherein a molar ratio of ethene to ethane in the non-condensable hydrocarbons ranges from about 0.001 to about 0.15.

20 2285. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is nitrogen.

25 2286. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is oxygen.

30 2287. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and wherein less than about 1 % by weight, when calculated on an atomic basis, of the condensable hydrocarbons is sulfur.

35 2288. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons comprise oxygen containing compounds, and wherein the oxygen containing compounds comprise phenols.

40 2289. The method of claim 2270, further comprising producing a mixture from the formation, wherein the produced mixture comprises condensable hydrocarbons, and

wherein greater than about 20 % by weight of the condensable hydrocarbons are aromatic compounds.

24
2290. The method of claim 2270, further comprising producing a mixture from the
5 formation, wherein the produced mixture comprises condensable hydrocarbons, and
wherein less than about 5 % by weight of the condensable hydrocarbons comprises multi-
ring aromatics with more than two rings.

22
2291. The method of claim 2270, further comprising producing a mixture from the
10 formation, wherein the produced mixture comprises condensable hydrocarbons, and
wherein less than about 0.3 % by weight of the condensable hydrocarbons are
asphaltenes.

23
2292. The method of claim 2270, further comprising producing a mixture from the
15 formation, wherein the produced mixture comprises condensable hydrocarbons, and
wherein about 5 % by weight to about 30 % by weight of the condensable hydrocarbons
are cycloalkanes.

Sub 67
20 2293. The method of claim 2270, further comprising producing a mixture from the
formation, wherein the produced mixture comprises a non-condensable component,
wherein the non-condensable component comprises hydrogen, wherein the hydrogen is
greater than about 10 % by volume of the non-condensable component, and wherein the
hydrogen is less than about 80 % by volume of the non-condensable component.

25 25 2294. The method of claim 2270, further comprising producing a mixture from the
formation, wherein the produced mixture comprises ammonia, and wherein greater than
about 0.05 % by weight of the produced mixture is ammonia.

26
30 2295. The method of claim 2270, further comprising producing a mixture from the
formation, wherein the produced mixture comprises ammonia, and wherein the ammonia
is used to produce fertilizer.

2296. The method of claim 2270, further comprising controlling a pressure within at least a majority of the selected section of the formation, wherein the controlled pressure is at least about 2.0 bar absolute.
- 5 2297. The method of claim 2270, further comprising controlling formation conditions to produce a mixture from the formation, wherein a partial pressure of H_2 within the mixture is greater than about 0.5 bar.
- 10 ^{Sub} 2298. The method of claim 2270, further comprising producing a mixture from the formation, wherein the partial pressure of H_2 within the mixture is measured when the mixture is at a production well.
- 15 2299. The method of claim 2270, further comprising altering a pressure within the formation to inhibit production of hydrocarbons from the formation having carbon numbers greater than about 25.
- 20 2300. The method of claim 2270, further comprising producing a mixture from the formation and controlling formation conditions by recirculating a portion of hydrogen from the mixture into the formation.
- 25 2301. The method of claim 2270, further comprising:
providing hydrogen (H_2) to the heated section to hydrogenate hydrocarbons within the section; and
heating a portion of the section with heat from hydrogenation.
- 30 2302. The method of claim 2270, further comprising:
producing hydrogen and condensable hydrocarbons from the formation; and
hydrogenating a portion of the produced condensable hydrocarbons with at least a portion of the produced hydrogen.

Sub 04

34

2303. The method of claim 2270, wherein allowing the heat to transfer comprises increasing a permeability of a majority of the selected section to greater than about 100 millidarcy.

Sub 7

~~2304. The method of claim 2270, wherein allowing the heat to transfer comprises substantially uniformly increasing a permeability of a majority of the selected section.~~

~~2305. The method of claim 2270, further comprising controlling the heat to yield greater than about 60 % by weight of condensable hydrocarbons, as measured by the Fischer Assay.~~

10

Sub 8

~~2306. The method of claim 2270, further comprising producing a mixture in a production well, and wherein at least about 7 heat sources are disposed in the formation for each production well.~~

15

~~2307. The method of claim 2270, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, and wherein the unit of heat sources comprises a triangular pattern.~~

20

~~2308. The method of claim 2270, further comprising providing heat from three or more heat sources to at least a portion of the formation, wherein three or more of the heat sources are located in the formation in a unit of heat sources, wherein the unit of heat sources comprises a triangular pattern, and wherein a plurality of the units are repeated over an area of the formation to form a repetitive pattern of units.~~

25

~~2309. A method of treating a hydrocarbon containing formation in situ, comprising:
providing heat from one or more heat sources to at least a portion of the formation;~~

30

~~allowing the heat to transfer from the one or more heat sources to a selected section of the formation; and~~